


Abbreviations used on this Material Safety Data Sheet:

N/av. = Not available, N/ap. = Not applicable, ppm = parts per million, TLV = Threshold Limit Value.

NFPA Hazard Rating: 4-Extreme, 3-High, 2-Moderate, 1-Slight, 0-None, X-Blank

SECTION I - IDENTIFICATION OF THE MATERIAL AND SUPPLIER				
PRODUCT NAME:	DE-cide™			4 - extreme 3 - high 2 - moderate 1 - slight 0 - insignificant
OTHER NAMES:	Diatomaceous Earth Amorphous Silica			
MATERIAL USE:	Insecticide, Dessicant		NFPA HAZARD RATING: Health - 1, Flammability - 0, Reactivity - 1  PMRA Reg No. 27265 Commercial Insecticide	
MANUFACTURER'S NAME:	Absorbent Products Ltd			
STREET ADDRESS:	724 East Sarcee St.			
CITY/PROVINCE:	Kamloops, BC			
POSTAL CODE:	V2H 1E7			
EMERGENCY TELEPHONE NUMBER:	1-800-667-0336			
SECTION II - HAZARD IDENTIFICATION				
SUMMARY: Prolonged and repeated exposure to excessive concentrations of this product's dust, or any nuisance dust, can cause chronic pulmonary disease. Dust contact with eyes may cause temporary scratchiness or redness. Long term exposure can cause silicosis. The NTP (National Toxicology Program) and IARC (International Agency for Research on Cancer) has determined that crystalline silica inhaled from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure. A single exposure will not result in serious adverse effects.				
 				
MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED: Pre-existing upper respiratory and lung disease, such as, but not limited to: Bronchitis, emphysema, and asthma.				
TARGET ORGAN(S): Lungs, Eyes.				
See SECTION X1 - TOXICOLOGICAL INFORMATION				
SECTION III - COMPOSITION OF SUBSTANCE				
HAZARDOUS INGREDIENTS	%	CAS NUMBER	OSHA PEL (ACGIH TLV)	LD50/ LC 50 SPECIES AND ROUTE
Naturally Occurring Diatomaceous Earth (Typical Analysis = 67% Silicon Dioxide)	100%	61790-53-2	See Section VIII	N/av.
Free Crystalline Silica or Silica, quartz (Occurs naturally in Diatomaceous Earth)	<1%	14808-60-7	See Section VIII	N/av.
For sampling silica dusts refer to NIOSH Analytical Method 7500 or OSHA method ID 142				
SECTION IV - FIRST AID MEASURES				
Inhalation:	Remove victim to fresh air. If breathing has stopped, a trained person should perform artificial respiration. Acute inhalation can cause dryness of the nasal passage and congestion of the upper respiratory tract.			
Ingestion:	Do not induce vomiting. Short-term exposure not considered harmful. Drink generous amounts of water to reduce bulk and drying effects.			
Eyes:	Wash with large quantities of water. Consult physician if irritation persists. May cause irritation/inflammation.			
Skin:	May cause dryness. Remove contaminated clothing. Wash with soap and water until clean. Use moisture renewing lotions if dryness persists. Product is not absorbed through or by the skin.			

SECTION V - FIREFIGHTING MEASURES				
Flammability	No			
Means of Extinction	N/ap.	Upper Flammibility Limit (% by Volume)	N/ap.	
Flashpoint (Method)	Non Flammable	Lower Flammibility Limit (% by Volume)	N/ap.	
Autoignition temperature	N/ap.	Extinguishing Media	N/ap.	
Hazardous Combustion Products	N/ap.	Special Procedures	N/ap.	
Explosion Data				
Sensitivity to Impact	No	Sensitivity to Static Discharge	No	
SECTION VI - ACCIDENTAL RELEASE MEASURES				
PROCEDURE FOR SPILLS / LEAKS:	Avoid creating further dust. Vacuum with equipment fitted with a filter. Alternatively, wet sweep or wash away. Dispose of in accordance with local, State, and Federal Regulations.			
SECTION VII - HANDLING AND STORAGE				
HANDLING PROCEDURES				
Avoid creating dust. Repair or properly dispose of broken bags. Use wet process or enclosed handling.				
STORAGE REQUIREMENTS				
Store in a dry place to maintain. Keep containers closed and in good condition. Repair damaged containers.				
SECTION VIII - EXPOSURE CONTROLS AND PERSONAL PROTECTION				
PERMISSABLE EXPOSURE LIMITS:	OSHA PEL	ACGIH	OHS	OHS STEL
(for airborne, nuisance dusts)	8 hr TWA	TLV	8 hr TWA	
Diatomaceous earth				
Total dust	15 mg/m ³	Not detected	4 mg/m ³	n/a
Respirable dust	5 mg/m ³	Not detected	1.5 mg/m ³	n/a
Crystalline quartz (respirable)	0.1 mg/m ³	0.1 mg/m ³	0.025mg/m ³	n/a
EFFECTS OF CHRONIC EXPOSURE TO PRODUCT. Exposure to quantities of crystalline silica dust, in the forms of quartz, cristobalite or tridymite, may be occur when in the presence of airborne dust. If the dust concentration levels are in excess of the OSHA Permissible Limit (PEL-TWA 8hrs) of 0.05mg/m3 or the ACGIH Threshold Limit Value (TLV) of 0.05mg/m3, the crystalline silica present is a known cause of silicosis, a progressive, sometimes fatal, lung disease. From the International Agency for Research on Cancer (IARC), a 2012 review of "Silica Dust, Crystalline, in the form of Quartz or Cristobalite" coded Monograph 100C concluded that Crystalline silica in the form of quartz or cristobalite dust is carcinogenic to humans (Group 1).				
ENGINEERING CONTROLS (SPECIFY, E.G. VENTILATION, ENCLOSED PROCESS)				
Control within recommended TLV/PEL, mechanical filtration to minimize dust. Refer to ACGIH publication "Industrial Ventilation" or similar publications for design of ventilation systems.				
PERSONAL PROTECTIVE EQUIPMENT				
GLOVES	Not needed under normal conditions of use.			
EYE	Use protective goggles in high dust conditions.			
FOOTWEAR	As required on jobsite.			
CLOTHING	Wear coveralls in high dust conditions.			
RESPIRATOR	Avoid breathing dust. See instructions below			
Bureau of Mines or NIOSH approved respirators for protection against pneumoconiosis producing dusts recommended when dust is present. If the dust concentration is less than ten (10) times the Permissible Exposure Limit (PEL) use quarter or half mask respirator (N95) with replacement dust filter or single use dust respirator with valve. If dust concentration is greater than ten (10) times and less than one hundred (100) times the PEL use full faceplate respirator with replaceable dust filter (N95 filter); if greater than one hundred (100) and less than two hundred (200) times the PEL use power air purifying (positive pressure) respirator with replaceable filter (N95 filters); if greater than two hundred (200) times the PEL use type C, automatic-air respirator, continuous flow type (positive pressure), with full facepiece, head or helmet.				

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES			
PHYSICAL STATE	solid	ODOR AND APPEARANCE	No odor, Buff/grey powder
VAPOR PRESSURE (mm Hg)	N/ap.	DENSITY (20 degrees Celcius)	35lb\cu. ft. +/- 5
VAPOR DENSITY (Air = 1)	N/ap.	SOLUBILITY IN WATER	Insoluble, forms
SPECIFIC GRAVITY (Water=1)	2.1		colloidal suspension
FREEZING POINT	N/ap.	pH	5.5 - 6.5
BOILING POINT	N/ap.	EVAPORATION RATE	N/ap.
SECTION X - STABILITY AND REACTIVITY			
CHEMICAL STABILITY (IF NO, UNDER WHICH CONDITIONS)	YES	X	
	NO		
INCOMPATIBILITY WITH OTHER SUBSTANCES (IF YES, SPECIFY)	YES	X	Hydrofluoric acid - silica may react violently
	NO		
REACTIVITY, AND UNDER WHAT CONDITIONS	N/ap.		
HAZARDOUS DECOMPOSITION PRODUCTS	N/ap.		
CONDITIONS TO AVOID	None in Designed Use		
SECTION XI - TOXICOLOGICAL INFORMATION			
PRIMARY ENTRY ROUTE(S):			
Eyes:	May cause temporary irritation or inflammation.		
Skin:	May cause dryness with continued exposure.		
Ingestion:	Not considered harmful, by mouth, throat, and/or stomach. Minor irritation may occur.		
Inhalation:	Persistent dry cough, throat irritation and labored breathing on exertion are symptomatic of exposure to airborne dust. Exposure may aggravate existing upper respiratory tract diseases such as asthma, bronchitis or emphysema. Acute (short term) exposure to dust levels exceeding the PEL may cause irritation of respiratory tract resulting in a dry cough. Eyes may develop redness and become itchy. Chronic (long term) exposure to crystalline silica contained by airborne diatomaceous earth, where levels are higher than TLV's, may lead to the development of silicosis, other respiratory problems, or some forms of cancer. From the International Agency for Research on Cancer (IARC), in a 2012 review of SILICA DUST, CRYSTALLINE, IN THE FORM OF QUARTZ OR CRISTOBALITE (monograph 100C) concluded that "Crystalline Silica in the form of quartz or cristobalite dust is <i>carcinogenic to humans</i> (group 1)." The NTP (National Toxicology Program) has determined that "Respirable crystalline silica, primarily quartz dust occurring in industrial and occupational settings , is know to be a human carcinogen."		
SECTION XII - ECOLOGICAL INFORMATION			
Product is generally considered chemically inert in the environment. Used product that has become contaminated may have significantly different characteristics than uncontaminated product, and should be reevaluated accordingly. Dispose of in accordance with Local, State, and Federal regulations.			
SECTION XIII - DISPOSAL CONSIDERATIONS			
Uncontaminated waste is not hazardous as defined by the Resource Conservation and Recovery Act (RCRA, 40 CFR261). Contaminated waste must be evaluated based on contamination source. Consult local agencies as needed. Dispose of in accordance with Local, State, and Federal regulations.			
SECTION XIV - TRANSPORTATION INFORMATION			
DOT Shipping Name: Not Regulated by DOT		Canada TDG: Not Regulated by TDG	
DOT Hazard Class:	n/a	Hazard Class:	n/a
Identification #:	n/a	UN #:	n/a

SECTION XV - REGULATORY INFORMATION		
OSHA:	This material is considered hazardous. See section 11.	WHMIS: Uncontrolled product according to WHMIS classification criteria
EINECS:	Not Listed	CND DSL: This product is listed on the DSL
TSCA:	This material is listed in the TSCA inventory and is not otherwise regulated by TSCA sec 4,5,6,7, or 12	NTP: "Respirable crystalline silica, primarily quartz dust occurring in industrial and occupational settings, is know to be a human carcinogen."
Calif Prop 65:	Listed: Crystalline Silica (airborne particles of respirable size)	RCRA: This material is not defined as hazardous waste
SECTION XVI - OTHER INFORMATION		
PREPARED BY: Quality Control Staff, Absorbent Products Ltd. PHONE NUMBER: 1-800-667-0336 DATE: January, 2016 All information presented herein is believed to be accurate; however, it is the user's responsibility to determine in advance of need that the information is current and suitable for their circumstances. No warranty or guarantee, expressed or implied is made by Absorbent Products Ltd., as to the information, or as to the safety, toxicity or the effect of this product.		